

SERIE 116-PCD

116-PCD

AVO - Wheel with conductive polyamide for industry, diameter 180mm ean 28033

Material: Conductive Polyamide

Core: Conductive polyamide 6

Application field: Industry

Description:

Heavy Duty wheel with conductive Polyamide 6. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plan bore.

Product line: Antistatic/Conductive

EAN13:8018793280334

EAN5:28033

Article code:05116CD180SCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 560 DaN

Rotation: Ball bearing

Hardness scale: Shore D

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	57
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X19
Dynamic load capacity (DaN)	560
Colour	Black
Material	Conductive Polyamide
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/