

SERIE 46P

46P

AVO - Wheel with puncture-proof polyurethane for industry, diameter 200mm ean 21121

Material: Puncture-proof Polyurethane

Core: Steel

Application field: Industry

Description:

Flat free wheel with polyurethane tyre and grey painted steel flanges. Hub on roller bearings.

Product line: Pneumatic

EAN13:8018793211215

EAN5:21121

Article code:19046PU201GRF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Yellow
Material	Puncture-proof Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/