

SERIE 46P

46P

AVO - Wheel with puncture-proof polyurethane for industry,
diameter 260mm ean 17198

Material: Puncture-proof
Polyurethane

Core:
Steel

Application field:
Industry

Description:

Flat free wheel with polyurethane tyre and grey painted steel flanges. Hub on roller bearings.

Product line: Pneumatic

EAN13:8018793171984

EAN5:17198

Article code:19046PU260GRF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	75
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Yellow
Material	Puncture-proof Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/