

SERIE 41PG

41PG

AVO - Wheel with puncture-proof polyurethane for industry,
diameter 260mm ean 17809

Material: Puncture-proof
Polyurethane

Core:
Polypropylene

Application field:
Industry

Description:

Flat free wheel with polyurethane tyre and thermoplastic material centre. Plain bore.

Product line: Pneumatic

EAN13:8018793178099

EAN5:17809

Article code:19041PU260GBF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 75 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	75
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	75
Colour	Grey
Material	Puncture-proof Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/