

SERIE S46VTP

S46VTP

AVO - Wheel with puncture-proof polyurethane for industry,
diameter 350mm ean 17495

Material: Puncture-proof
Polyurethane

Core:
Steel

Application field:
Industry

Description:

Flat free wheel with polyuretane tyre for wheelbarrow with gray painted steel flanges. Wheel is supplied without axle material.

Product line: Pneumatic

EAN13:8018793174954

EAN5:17495

Article code:8304600350VTP



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 100 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	350
Band width (mm)	60
Hub width (mm)	155
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Yellow
Material	Puncture-proof Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/