

SERIE 14AS

# 14AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 125mm ean 21658

**Material:** Avoantistatic Polyurethane    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

**Product line:** Antistatic/Conductive

**EAN13:**8018793216586    **EAN5:**21658    **Article code:**09014AS125YCU



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 350 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	350
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/