

SERIE 14AS

14AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 125mm ean 22651

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Product line: Antistatic/Conductive

EAN13:8018793226516

EAN5:22651

Article code:09014AS125SCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	25
Hub width (mm)	25
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	47X12
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/