

SERIE 14AS

14AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 80mm ean 17866

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Product line: Antistatic/Conductive

EAN13:8018793178662

EAN5:17866

Article code:09014AS080LCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 20 |
| Hub width (mm) | 10 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 32X10 |
| Dynamic load capacity (DaN) | 150 |
| Colour | Grey |
| Material | Avoantistatic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | / |
| Ground clearance (mm) | / |
| Castor hole (mm) | / |
| Static load capacity (DaN) | / |
| Structure | / |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | / |