

SERIE 18AS-B

74A-B-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 100mm ean 23481

Material: Avoantistatic Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all duty castors. The measured electrical characteristic that are guaranteed by the material and production process can be summarized by the inequality.

Medium duty castors:

Product line: Antistatic/Conductive

EAN13:8018793234818 **EAN5:**23481 **Article code:**09074A0100ABG

Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized