

SERIE 18AS-X

37XANT-ASX

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 100mm ean 25155

Material: Avoantistatic Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all duty castors. The measured electrical characteristic that are guaranteed by the material and production process can be summarized by the inequality: $R \leq 50 \text{ Mega Ohm}$.

Medium duty castors:

Product line: High temperature

EAN13:8018793251556 **EAN5:**25155 **Article code:**090370A11XACG

Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized