

SERIE 14AS

## 27A-AS

**AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 150mm**

**Material:** Avoantistatic Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:/ EAN5:/ Article code:**11027A0150YCG



### Features

|                                 |                                |                                       |
|---------------------------------|--------------------------------|---------------------------------------|
| <b>Minimum temperature:</b> -20 | <b>Maximum temperature:</b> 80 | <b>Dynamic load capacity:</b> 600 DaN |
| <b>Rotation:</b> Ball bearing   | <b>Hardness scale:</b> Shore A | <b>Hardness:</b> 91                   |

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                                    |                            |
|------------------------------------|----------------------------|
| <b>Diameter (mm)</b>               | 150                        |
| <b>Band width (mm)</b>             | 50                         |
| <b>Hub width (mm)</b>              | 50                         |
| <b>Hub version</b>                 | Ball bearing               |
| <b>Wheel hole (mm)</b>             | 20                         |
| <b>Bearing seat (mm)</b>           | 47X14                      |
| <b>Dynamic load capacity (DaN)</b> | 600                        |
| <b>Colour</b>                      | Grey                       |
| <b>Material</b>                    | Avoantistatic Polyurethane |
| <b>Box pieces</b>                  | /                          |
| <b>Hardness scale</b>              | Shore A                    |
| <b>Hardness</b>                    | 91                         |

### Support data

|                                   |            |
|-----------------------------------|------------|
| <b>Plate size (mm)</b>            | 135X110    |
| <b>Plate hole spacing (mm)</b>    | 105X080    |
| <b>Plate hole size (mm)</b>       | 13X16      |
| <b>Offset (mm)</b>                | /          |
| <b>Ground clearance (mm)</b>      | 189        |
| <b>Castor hole (mm)</b>           | /          |
| <b>Static load capacity (DaN)</b> | 750        |
| <b>Structure</b>                  | Fixed      |
| <b>Version</b>                    | /          |
| <b>Brake</b>                      | /          |
| <b>Plain axle</b>                 | /          |
| <b>Stem type</b>                  | /          |
| <b>Finishing</b>                  | Galvanized |