

SERIE 14AS

22A-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 150mm ean 22351

Material: Avoantistatic
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:8018793223515

EAN5:22351

Article code:09022A0151LCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Purple
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized