

SERIE 14AS

# 30YBISB-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 150mm ean 23205

**Material:** Avoantistatic Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

**Product line:** Antistatic/Conductive

**EAN13:**8018793232050

**EAN5:**23205

**Article code:**21030BF150SCG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 400 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	150
<b>Band width (mm)</b>	30
<b>Hub width (mm)</b>	30
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	17
<b>Bearing seat (mm)</b>	40X12
<b>Dynamic load capacity (DaN)</b>	400
<b>Colour</b>	Grey
<b>Material</b>	Avoantistatic Polyurethane
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	91

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	50
<b>Ground clearance (mm)</b>	205
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	500
<b>Structure</b>	Swivel
<b>Version</b>	Axle with brake
<b>Brake</b>	Rear
<b>Plain axle</b>	22X50
<b>Stem type</b>	Stem(on request threaded stem) Plain axle
<b>Finishing</b>	Black painted