

SERIE 18AS

38-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 160mm

Material: Avoantistatic
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with antistatic Polyurethane thread AVOANTISTATIC 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:/ **EAN5:/** **Article code:**1103800160ACG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	216
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized