

SERIE 18AS

## 38A-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 200mm ean 18519

**Material:** Avoantistatic Polyurethane

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel coated with antistatic Polyurethane thread AVOANTISTATIC 91 Shore A and aluminum centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793185196 **EAN5:**18519 **Article code:**11038A0200ACG



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 560 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	560
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	700
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized