

SERIE 14AS

33Y-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 200mm ean 22670

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Antistatic/Conductive

EAN13:8018793226707

EAN5:22670

Article code:2103300200XCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	2000
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	270
Castor hole (mm)	/
Static load capacity (DaN)	2500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted