

SERIE 14AS

30YA-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 300mm ean 21256

Material: Avoantistatic
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Antistatic/Conductive

EAN13:8018793212564

EAN5:21256

Article code:21030A0300LCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	1800
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	/
Ground clearance (mm)	370
Castor hole (mm)	/
Static load capacity (DaN)	2250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted