

SERIE 14AS

27-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 80mm

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:/ **EAN5:/** **Article code:**11027008036CG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	36
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	9X12
Offset (mm)	36
Ground clearance (mm)	118
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized