

SERIE 14AS

24-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 80mm ean 17868

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with antistatic cast polyurethane tread AVOANTISTATIC 91 Shore A and mechanical cast iron centre. Hub on shielded ball bearing assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13:8018793178686

EAN5:17868

Article code:0902400080LCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	20
Hub width (mm)	10
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized