

SERIE 14V

14V

AVO - Wheel with avobio polyurethane for industry, diameter 200mm

Material: Avobio
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOBIO 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer. Ideal for purification systems or environments where there is the presence of oils and acids. The 14V wheel can be assembled with all medium, heavy and extra heavy-duty castors, including twin wheel versions.

Product line: Polyurethane

EAN13:/ **EAN5:/** **Article code:**09014SI20080V



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1600 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	80
Hub width (mm)	80
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	1600
Colour	Green
Material	Avobio Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/