

SERIE 14ECC

14ECC

AVO - Wheel with avolan polyurethane for industry, diameter 100mm

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel with Polyurethane tread AVOLAN, 91 Shore A, and cast iron wheel center. Hub on shielded ball bearings and eccentric axle.

Product line: Elevators

EAN13:/ EAN5:/ Article code:09014ECC10130



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	Eccentric axle
Finishing	/