

SERIE 600

600

AVO - Wheel with avolan polyurethane for industry, diameter 250mm ean 15055

**Material:** Avolan  
Polyurethane

**Core:** Electro-welded  
steel

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and electro-welded steel centre. Hub on shielded and sealed ball bearings.

**Product line:** Polyurethane

**EAN13:**8018793150552

**EAN5:**15055

**Article code:**0906002250LCU



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 2500 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 250                 |
| Band width (mm)             | 100                 |
| Hub width (mm)              | 100                 |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 30                  |
| Bearing seat (mm)           | 62X17               |
| Dynamic load capacity (DaN) | 2500                |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

## Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |