

SERIE 14CH

14CH

AVO - Wheel with avolan polyurethane for industry, diameter 300mm ean 20433

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Heavy duty drive wheel coated with cast Polyurethane AVOLAN 91 Shore A and black painted mechanical cast iron, aluminium or steel centre. Hub with keyway according to DIN6885.

Product line: Polyurethane

EAN13:8018793204330

EAN5:20433

Article code:09014CH300207



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2200 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Plain bore
Wheel hole (mm)	72
Bearing seat (mm)	/
Dynamic load capacity (DaN)	2200
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/