

SERIE 14CH

14CH

AVO - Wheel with avolan polyurethane for industry, diameter 300mm ean 21147

Material: Avolan Polyurethane **Core:** Steel **Application field:** Industry

Description:

Heavy duty drive wheel coated with cast Polyurethane AVOLAN 91 Shore A and black painted mechanical cast iron, aluminium or steel centre. Hub with keyway according to DIN6885.

Product line: Polyurethane

EAN13:8018793211475 **EAN5:**21147 **Article code:**09014CH30060U



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 2100 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	60
Hub width (mm)	60
Hub version	Plain bore
Wheel hole (mm)	50
Bearing seat (mm)	/
Dynamic load capacity (DaN)	2100
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/