

SERIE 11ECC

11ECC

AVO - Wheel with avolan polyurethane for industry, diameter 80mm

Material: Avolan
Polyurethane

Core: Cast
Iron


Application field:
Industry

Description:

Roller with polyurethane tread AVOLAN, 91 Shore A and steel core. Hub on shielded ball bearings and eccentric axle.

Product line: Elevators

EAN13:/ **EAN5:/** **Article code:**09011ECC08025



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	25
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	400
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	Eccentric axle
Finishing	/