

SERIE 14

22

**AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 100mm ean 06113**

**Material:** Avolan Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane

**EAN13:**8018793061131

**EAN5:**06113

**Article code:**0902200100LCU



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 100                 |
| Band width (mm)             | 30                  |
| Hub width (mm)              | 30                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 15                  |
| Bearing seat (mm)           | 35X11               |
| Dynamic load capacity (DaN) | 120                 |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 8,5X12     |
| Offset (mm)                | 37         |
| Ground clearance (mm)      | 128        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 150        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |