

SERIE 14

30YB

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 100mm ean 11436

Material: Avolan Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114363 **EAN5:**11436 **Article code:**21030B0100LCU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 250 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 100 |
| Band width (mm) | 30 |
| Hub width (mm) | 30 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | 35X11 |
| Dynamic load capacity (DaN) | 250 |
| Colour | Yellow |
| Material | Avolan Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|---------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 36 |
| Ground clearance (mm) | 150 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 320 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Plain axle | 22X50 |
| Stem type | Plain axle |
| Finishing | Black painted |