Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

**SERIE 18A** 

# 38BISB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 100mm ean 14578

**Material:** Avolan Polyurethane

Core: Aluminum Application field:

Industry

#### Description

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

#### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793145787

EAN5:14578

Article code:11038BF100LCU



### **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Ball bearing Hardness scale: Shore A

Hardness: 91

## **Flooring**

- Asphalt
- ConcreteGrid
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	250
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	1
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized