

SERIE 18A

# 38B

**AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 125mm ean 06389**

**Material:** Avolan  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793063890 **EAN5:**06389 **Article code:**11038B0125ACU



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 250 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	125
<b>Band width (mm)</b>	30
<b>Hub width (mm)</b>	30
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	15
<b>Bearing seat (mm)</b>	35X11
<b>Dynamic load capacity (DaN)</b>	250
<b>Colour</b>	Yellow
<b>Material</b>	Avolan Polyurethane
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	91

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	45
<b>Ground clearance (mm)</b>	161
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	320
<b>Structure</b>	Swivel
<b>Version</b>	Axle
<b>Brake</b>	/
<b>Plain axle</b>	22X50
<b>Stem type</b>	Stem(on request threaded stem) Plain axle
<b>Finishing</b>	Galvanized