

SERIE 14

## 22A

**AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 125mm ean 13915**

**Material:** Avolan  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793139151

**EAN5:**13915

**Article code:**09022A0125YCU



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 170 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 125                 |
| Band width (mm)             | 35                  |
| Hub width (mm)              | 35                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 20                  |
| Bearing seat (mm)           | 47X14               |
| Dynamic load capacity (DaN) | 170                 |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 8,5X12     |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 155        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 220        |
| Structure                  | Fixed      |
| Version                    | /          |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |