

SERIE 18A

37B

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 125mm ean 14486

Material: Avolan
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793144865

EAN5:14486

Article code:09037B0125LCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized