

SERIE 18A

37A

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 125mm ean 18281

Material: Avolan
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793182812 **EAN5:**18281 **Article code:**09037A0125AC3



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 170 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized