

SERIE 14

33YDIR

AVO - Wheel made of avolan polyurethane with steel castor for industry, diameter 125mm ean 24088

Material: Avolan Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

Product line: Polyurethane

EAN13: 8018793240888 **EAN5:** 24088 **Article code:** 21033DI125X3U



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 750 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	750
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	60
Ground clearance (mm)	197
Castor hole (mm)	/
Static load capacity (DaN)	940
Structure	Swivel
Version	Plate
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted