

SERIE 14

27A

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 150mm ean 06300

Material: Avolan Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793063005

EAN5:06300

Article code:11027A0150YCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 600 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 150 |
| Band width (mm) | 50 |
| Hub width (mm) | 50 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 600 |
| Colour | Yellow |
| Material | Avolan Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | 135X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | / |
| Ground clearance (mm) | 189 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 750 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |