

SERIE 14

## 24ANTF

AVO - Wheel with avolan polyurethane and steel castor for industry,  
diameter 150mm ean 10398

**Material:** Avolan Polyurethane    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:** 8018793103985    **EAN5:** 10398    **Article code:** 09024FF150SCU



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 200 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 150                 |
| Band width (mm)             | 30                  |
| Hub width (mm)              | 30                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 17                  |
| Bearing seat (mm)           | 40X12               |
| Dynamic load capacity (DaN) | 200                 |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

### Support data

|                            |                      |
|----------------------------|----------------------|
| Plate size (mm)            | /                    |
| Plate hole spacing (mm)    | /                    |
| Plate hole size (mm)       | /                    |
| Offset (mm)                | 45                   |
| Ground clearance (mm)      | 179                  |
| Castor hole (mm)           | 12                   |
| Static load capacity (DaN) | 250                  |
| Structure                  | Swivel               |
| Version                    | Bolt hole with brake |
| Brake                      | Front                |
| Plain axle                 | /                    |
| Stem type                  | /                    |
| Finishing                  | Galvanized           |