

SERIE 18A

38BISB

AVO - Wheel made of avolan polyurethane with steel castor for industry, diameter 150mm ean 10935

Material: Avolan Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793109352 **EAN5:**10935 **Article code:**11038BF150ACU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	184
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem)
Finishing	Galvanized