Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 150mm ean 11428

Material: Avolan Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114288

EAN5:11428

Article code:21030BF150LCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 450 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	450
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	1
Static load capacity (DaN)	570
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted