

SERIE 14

30YBISB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 150mm ean 11430

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114301 **EAN5:**11430 **Article code:**21030BF150XCU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 500 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Black painted