

SERIE 14

30YB

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 150mm ean 11443

Material: Avolan Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114431 **EAN5:**11443 **Article code:**21030B0150SCU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	400
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted