

SERIE 14

33YDIR

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 150mm ean 22345

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793223454

EAN5:22345

Article code:21033DI150GCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	60
Ground clearance (mm)	210
Castor hole (mm)	/
Static load capacity (DaN)	1250
Structure	Swivel
Version	Plate with brake Plate
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted