

SERIE 18A

38BISB

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 160mm ean 14568

Material: Avolan Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793145688 **EAN5:**14568 **Article code:**11038BF160ACU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 500 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 160 |
| Band width (mm) | 50 |
| Hub width (mm) | 60 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | 47X14 |
| Dynamic load capacity (DaN) | 500 |
| Colour | Yellow |
| Material | Avolan Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 57 |
| Ground clearance (mm) | 209 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 630 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |