

SERIE 14

27B

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 175mm ean 06330

Material: Avolan Polyurethane

Core: Cast Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793063302

EAN5:06330

Article code:11027B0175SCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 600 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	175
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	600
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	231
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized