

SERIE 14

# 30YB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 175mm ean 11446

**Material:** Avolan Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793114462    **EAN5:**11446    **Article code:**21030B0175LCU



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 650 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	650
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	248
Castor hole (mm)	/
Static load capacity (DaN)	820
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Black painted