Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 175mm ean 11447

Material: Avolan Polyurethane

Core: Cast Iron

Application field:

Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:** 

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114479

EAN5:11447

Article code:21030B0175SCU



## **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 600 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 91

## **Flooring**

- Asphalt
- Concrete • Grid
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	600
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	248
Castor hole (mm)	1
Static load capacity (DaN)	750
Structure	Swivel
Version	Axle
Brake	I
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted