

SERIE 14

## 24ANTB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 200mm ean 10381

**Material:** Avolan  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793103817 **EAN5:**10381 **Article code:**09024BF200SCU



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

<b>Diameter (mm)</b>	200
<b>Band width (mm)</b>	40
<b>Hub width (mm)</b>	40
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	20
<b>Bearing seat (mm)</b>	47X14
<b>Dynamic load capacity (DaN)</b>	300
<b>Colour</b>	Yellow
<b>Material</b>	Avolan Polyurethane
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	91

### Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	55
<b>Ground clearance (mm)</b>	232
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	380
<b>Structure</b>	Swivel
<b>Version</b>	Axle with brake
<b>Brake</b>	Front
<b>Plain axle</b>	22X50
<b>Stem type</b>	Plain axle Stem(on request threaded stem)
<b>Finishing</b>	Galvanized