

SERIE 14

33YBIS

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 250mm ean 20064

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793200646 **EAN5:**20064 **Article code:**210330F250GCU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 2800 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 250 |
| Band width (mm) | 60 |
| Hub width (mm) | 60 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 2800 |
| Colour | Yellow |
| Material | Avolan Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 230X230 |
| Plate hole spacing (mm) | 190X190 |
| Plate hole size (mm) | 19 |
| Offset (mm) | 80 |
| Ground clearance (mm) | 320 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 3500 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |