

SERIE 14

33YDIR

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 250mm ean 21591

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793215916

EAN5:21591

Article code:21033DI250GCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	2800
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	80
Ground clearance (mm)	320
Castor hole (mm)	/
Static load capacity (DaN)	3500
Structure	Swivel
Version	Plate with brake Plate
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted