

SERIE 14

30YB

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 300mm ean 11452

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793114523

EAN5:11452

Article code:21030B0300LCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	1800
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	83
Ground clearance (mm)	370
Castor hole (mm)	/
Static load capacity (DaN)	2250
Structure	Swivel
Version	Axle
Brake	/
Plain axle	50X90
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted