

SERIE 14

33YDIRT

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 300mm ean 21656

Material: Avolan Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of heavy-gauge pressed and welded steel, swivel-mounted on a thrust bearing and tapered roller bearings, with top plate and directional lock. Black epoxy coating. Equipped with ISO Twist Lock fitting and 4-position directional lock.

Product line: Polyurethane

EAN13:8018793216562 **EAN5:**21656 **Article code:**21T33DI300GCU



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 4000 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	4000
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	83
Ground clearance (mm)	419
Castor hole (mm)	/
Static load capacity (DaN)	5000
Structure	Swivel
Version	Plate
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted