

SERIE 14

24

**AVO - Wheel made of avolan polyurethane with steel castor for industry, diameter 300mm ean 23372**

**Material:** Avolan Polyurethane    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane

**EAN13:**8018793233729    **EAN5:**23372    **Article code:**0902400300LCU



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 450 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	450
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	85
Ground clearance (mm)	340
Castor hole (mm)	/
Static load capacity (DaN)	570
Structure	Swivel
Version	Plate with brake
Brake	Rear
Stem	/
Stem type	/
Finishing	Galvanized